


CIRCLE S PRODUCTS AIR FLOW CHART



$$\text{Actual Pressure Drop} = \left[\frac{\text{Application's Equivalent Air Flow SCFM (Qc)}}{\text{Separator's Maximum Rated Air Flow SCFM}} \right]^2 \times \text{Rated Pressure Drop}$$

(obtain from scale on right side)

Circle S Products, Inc.
 PH: 734-675-2960
 FAX: 734-675-6577
 S9115

The Circle S Products air flow chart on the reverse side is based on SCFM (cubic feet per minute of air measured at standard conditions of 14.7 psia and 60°F). If any of the operating conditions are varied from the above, then correction factors must be applied.

To use the air flow chart for applications involving other gases or other than standard conditions the following equation must be solved for Q_C :

$$Q_C = C_{SG} \times F_g \times F_t$$

In the event that Q_{SG} is not provided in the proper form, any of the following equations may be used to arrive at the correct flow rate to insert in the above equation.

$$Q_{SG} = \frac{6.3 \times W}{MW}$$

$$Q_{SG} = \frac{35.37 \times Q_a \times P_a}{460 + T_a}$$

$$Q_{SG} \text{ (air only)} = .218 \times W$$

$$Q_{SG} = \frac{MMSCFD}{1440}$$

$$W = (\text{Pound mols/hour}) \times MW$$

EXPLANATION OF SYMBOLS

- F_g = Correction factor for specific gravity (see table at right)
- F_t = Correction factor for temperature (see table at far right)
- G = Specific gravity
- MMSCFD = Million standard cubic feet per day
- MW = Molecular weight
- P_a = Pressure (psia) at which volume is measured
- Q_a = Rate of flow-measured cubic feet per minute (ACFM)
- Q_C = Rate of flow-standard cubic feet per minute of equivalent air
- Q_{SG} = Rate of flow-standard cubic feet per minute
- T = Operating temperature (°F)
- T_a = Temperature (°F) at which volume is measured
- W = Rate of flow-pounds per hour

SPECIFIC GRAVITY CORRECTION FACTORS

GAS		M.W.	G	FG
Hydrogen	H ₂	2.0	0.069	0.344
Helium	He	4.0	0.138	0.452
Synthesis	75%H ₂ 25%N ₂	8.5	0.295	0.611
Coke Oven		11.0	0.379	0.679
*Methane	CH ₄	16.0	0.551	0.788
Ammonia	NH ₃	17.0	0.586	0.808
Steam (Water Vapor)	H ₂ O	18.0	0.621	0.826
*Natural Gas	75%CH ₄ 25%N ₂	19.0	0.655	0.844
Acetylene	C ₂ H ₂	26.0	0.897	0.957
Nitrogen	N ₂	28.0	0.95	0.986
Carbon Monoxide	C _o	28.0	0.95	0.986
Air		29.0	1.00	1.000
Flue Gas	81%N ₂ 19%CO ₂	31.0	1.08	1.027
Oxygen	O ₂	32.0	1.10	1.039
Argon	A	39.9	1.38	1.136
Propane	C ₂ H ₈	44.1	1.52	1.182
*Carbon Dioxide	CO ₂	44.0	1.52	1.181
Nitrous Oxide	N ₂ O	44.0	1.52	1.181
Butadiene	C ₄ H ₆	54.1	1.86	1.284
Sulphur Dioxide	SO ₂	64.1	2.21	1.374
Chlorine	C1 ₂	70.9	2.45	1.431
Freon 12	CC ₂ F ₂	120.9	4.17	1.770

- 1 psi = 2.036" Hg
- 1" Hg = .4912 psi
- 1 psi = 27.71" H₂O
- 1" H₂O = .03613 psi

NOTE

* For applications involving gases (above 500 PSI & 200°F) so marked, contact the home office to determine whether there is an additional correction factor for compressibility.

TEMPERATURE CORRECTION FACTORS

T	FT
- 20°F	0.904
- 10	0.917
0	0.929
10	0.941
20	0.953
30	0.965
40	0.977
50	0.989
60	1.000
70	1.012
80	1.023
90	1.034
95	1.040
100	1.046
105	1.051
110	1.057
120	1.068
130	1.079
140	1.090
150	1.101
160	1.112
170	1.121
180	1.133
190	1.143
200	1.154
250	1.206
300	1.256
400	1.353
500	1.445
550	1.490
600	1.533
700	1.618
800	1.701
900	1.780
1000	1.858

CIRCLE S PRODUCTS, INC.

PH: 734-675-2960
FAX: 734-675-6577

S9115